

# Euro Maintenance Oil - Natural

## Product Specification

### *Characteristics*

Bella Citta's Euro Maintenance Oil is a high quality product for all oiled surfaces. Euro Maintenance Oil is resistant to wine, beer, cola, coffee, tea, fruit juices, milk and water according to DIN 68861 1A. Resistant to saliva and sweat according to DIN 53160. Meets all the demands of children's toys according to EN 71.

Applications: All Oiled Flooring surfaces.

**Contains:** aliphatic hydrocarbons, castor oil, natural resin-ester, silicic acids, silicate pigments, zinc carbonate, microwax, bentonite, cobalt, zirconium, zinc and manganese octoate as drying components.

### *Technical Data*

**Working temperature:** not below 16°C (60.8°F).

**Drying time:** 6 to 12 hours (depending on temperature and ventilation).

**Usage:** 1 liter = approx. 70 m<sup>2</sup> (753.55 SF) in one coat.

**Storage:** Store in cool and dry area. After prior usage, dry layer of skin may form at the surface. Remove the skin layer prior to further use.

**Warning:** TO PREVENT SPONTANEOUS COMBUSTION AND/OR FIRE, SOAK ALL CLOTHS, RAGS OR ANY MAINTENANCE OIL APPLICATOR IN WATER AFTER USE. AFTER THOROUGHLY SOAKING IN WATER AND DRYING YOU CAN DISPOSE OF THE APPLICATOR.

EU-limit for this product (cat. A/f): 700 g/l (2010). This product contains max. 690 g/l VOC.

**Packing:** 1 liter (33.82 fl.oz)

### *Instructions for use*

The flooring surface must be dry, vacuumed well & free of any dust or grease. Then clean the flooring surface using a Bella Citta approved cleaner. Allow the cleaner to completely dry. Stir your Euro Maintenance Oil thoroughly prior to use. Next apply the Euro Maintenance Oil onto the flooring surface working in small areas at a time. The product should be applied in a thin and even layer with a clean cloth in the direction of the wood graining. Allow the product to thoroughly dry to the touch prior to walking on the surface. For larger areas we recommend using a buffing machine. Dribble the Euro Maintenance Oil on the flooring surface in the shape of a snake. Polish the product into the floor with the buffing machine using a thick white pad. Allow the product to thoroughly dry to the touch prior to walking on the surface.

*Above product information and recommendations are given in good faith and based on practical tests following long term research and development. We cannot assume responsibility for any work as the ultimate results depend on factors beyond our direct control. In cases of doubt always test the product in advance.*

1-855-BCFLOOR (223-5667)

[www.bellacittafloors.com](http://www.bellacittafloors.com)

